

**14"
UPCUT
CONCRETE
AND
ASPHALT
DRY CUT
DUST
CONTROL
SAWS**

MODEL #	SB-14G	SB-14E	ASB-14
PART #	48200	42600	47200
POWER	Gasoline	Electric	Air
ENGINE/ MOTOR	Honda GX390	5 HP, 230V/30A	5 HP, 180 cfm at 100 psi
PHASE	N/A	Single	N/A
AMPS	N/A	19.5	N/A
*RPMS	3600	3450	2500
LENGTH	57"	57"	57"
WIDTH	23.5"	23.5"	23.5"
HEIGHT	38"	38"	38"
WEIGHT	193 lbs	205 lbs	160 lbs
MAX CORD LENGTH	N/A	100 ft, 10 Gauge	N/A

**MAX
CUTTING
DEPTH
4 3/4"**



TWIST LOCK POWER CORD
Part# 101270



SB-14 Optional Water Tank Assembly
PART# 51090
PART# 56310

PRODUCT NOTES: 14" Blade capacity. Upcut blade rotation provides clean cut, and consistent depth. 7-gauge steel frame and undercarriage eliminates bending, and vibration.

REQUIRES 1 - 14" concrete or asphalt blade

IDEAL FOR:

- Expansion joint cleaning
- Short-run slab cutting
- Cured Contraction Joints
- Patch repairs in asphalt and concrete
- Trenching

STANDARD 2" VACUUM TUBE

Pair with EDCO's Vac-200



SB-14