

Quickly and Safely!






Leverage is your advantage for making tree stumps disappear.

SG1114/SG1314

With BlueBird's new SG1114 and SG1314 Stump Grinders, you can now remove stumps quickly and safely! This well-balanced design offers commercial power and high productivity. BlueBird's Stump Grinder maximizes cutting performance with its 14-inch diameter blade with carbide-tipped teeth, offering a variable cutting depth up to 12 inches.

Operator fatigue is reduced with its ergonomic handle. The unique, adjustable handle has four height adjustment positions to ensure operator comfort and a safe stance during all stages of stump removal. The compact design (27") and clean sight lines of the Stump Grinder make it easy to maneuver through narrow gates and other tight areas. Two user-friendly lift handles on each side of the unit allow two people to lift the unit into mini vans, trucks and large SUVs.

BlueBird's use of high-quality components like Gates HiPower® Double V Drive belt, NORAM™ automatic centrifugal clutch, and Hayes brake calipers ensure outstanding stump grinding results time after time, year after year.



BlueBird's innovative adjustable handle enables the operator to adjust the angle of the handle to maintain a safe and comfortable stance throughout the stump grinding job.

Specifications				
	•		SG1114	SG1314
	Power	Engine Brake	11 HP Honda with cyclone air filter and NORAM™ automatic centrifugal clutch Hayes disc brake, lever activated	13 HP Honda with cyclone air filter and NORAM™ automatic centrifugal clutch Hayes disc brake, lever activated
	Performance	Cut Depth Drive Belt	Variable, up to 12 inches with adjustable handle Direct Gates HiPower Double V-Belt BP54	Variable, up to 12 inches with adjustable handle Direct Gates HiPower Double V-Belt BP54
	Assembly	Construction Wheels Cutter Wheel Bearings	Welded 7-gauge steel frame 12" diameter pneumatic knobby tread (4.10-6 2-ply) Vertical 14 x 3/8" disk with 8 Tungsten carbide-tipped teeth with pockets Cast flange greasable	Welded 7-gauge steel frame 12" diameter pneumatic knobby tread (4.10-6 2-ply) Vertical 14x3/8" disk with 8 Tungsten carbide-tipped teeth with pockets Cast flange greasable
	Size	Width Length Height Weight Shipping Weight	27" (69cm) 62-73" (157-185cm) based on handle position 27-45" (68-114cm) based on handle position 252 lbs (114kg) 350 lbs (159kg)	27" (69cm) 62-73" (157-185cm) based on handle position 27-45" (68-114cm) based on handle position 252 lbs (114kg) 350 lbs (159kg)

BlueBird International, Inc. 1400 East 66th Avenue Denver, Colorado 80229 USA

PHONE 303-288-5880

TOLL FREE 1-800-808-BIRD (US only)

FAX 303-288-5899

TOLL FREE FAX 1-800-254-BIRD (US only)

WEBSITE www.bluebirdintl.com

EMAIL actioncenter@bluebirdintl.com

